

SECTION TABLE OF CONTENTS

DIVISION 10 - SPECIALTIES

SECTION 10800

WASHROOM ACCESSORIES

PART 1 GENERAL

- 1.1 DESCRIPTION
- 1.2 SUBMITTALS
- 1.3 DELIVERY, STORAGE, AND HANDLING
- 1.4 WARRANTY

PART 2 PRODUCTS

- 2.1 FLOOR MOUNTED TOILET
- 2.2 SINK
- 2.3 TOILET SEAT COVER DISPENSER
- 2.4 PAPER TOWEL DISPENSER AND WASTE RECEPTACLE
- 2.5 MIRROR SHELF
- 2.6 SOAP DISPENSER
- 2.7 TOILET TISSUE DISPENSER

PART 3 EXECUTION

- 3.1 GENERAL
- 3.2 TEMPORARY PROTECTION

-- End of Section Table of Contents --

## SECTION 10800

## WASHROOM ACCESSORIES

## PART 1 GENERAL

## 1.1 DESCRIPTION

The work in this section consists of furnishing all equipment, labor, and materials, and performing all work necessary to complete the design and to deliver, erect, install, and test the washroom accessories. Materials and equipment shall be the products of manufacturers regularly engaged in the manufacturer of said products. All like materials and equipment shall be by the same manufacturer. All permanent equipment shall be new and unused.

## 1.2 SUBMITTALS

Government approval is required for submittals with a "G" designation; submittals not having a "G" designation are for information only. When used, a designation following the "G" designation identifies the office that will review the submittal for the Government. The following shall be submitted in accordance with Section 01330 SUBMITTAL PROCEDURES:

## SD-01 Preconstruction Submittals

## Materials and Equipment; G

List of Materials and Equipment: Within 60 days after award of the contract and before any materials or equipment are purchased, a complete list of materials and equipment, including catalog cuts, to be incorporated into the work, together with the names and addresses of the manufacturers, their catalog numbers and trade names shall be submitted. Approval of the materials shall be based on the manufacturer's published ratings. Any materials and equipment listed which are not in accordance with the specification requirements shall be rejected.

## SD-02 Shop Drawings

## Contract drawings; G

The contract drawings covering the layout of washroom accessories are considered to be sufficiently detailed to permit the installation of the systems without necessity for further amplification by shop drawings. The Contractor shall carefully examine the drawings and shall be responsible for the proper installation. Any proposed departure from the layout details shown on the contract drawings which are necessitated by field conditions or other causes shall be submitted as shop drawings.

## Locations of washroom accessories; G

## SD-03 Product Data

### Accessory Items; G

Catalog Information shall be submitted for the stainless steel toilet, sink, toilet seat cover dispenser, paper towel dispenser and waste receptacle, mirror shelf, soap dispenser, toilet tissue dispenser and toilet seat-cover dispenser.

#### 1.3 DELIVERY, STORAGE, AND HANDLING

Toilet accessories shall be wrapped for shipment and storage, delivered to the jobsite in manufacturer's original packaging, and stored in a clean, dry area protected from construction damage and vandalism.

#### 1.4 WARRANTY

Manufacturer's warranties shall be furnished on all equipment supplied under this section which normally carry a warranty or guarantee. The period of the warranty shall be for one year, starting from the date of acceptance of the equipment, either for beneficial use of final acceptance, whichever is earlier and shall be against defective materials, design and workmanship. Upon receipt of notice from the Government of failure of any part or parts if this equipment during the warranty period, new parts shall be replaced and installed promptly by the Contractor.

### PART 2 PRODUCTS

#### 2.1 FLOOR MOUNTED TOILET

The floor mounted toilet shall be fabricated from stainless steel with satin finish. The toilet and appurtenances shall be installed in strict accordance with manufacturer's instructions.

#### 2.2 SINK

Wall mounted sink shall be of stainless steel with satin finish. The sink and appurtenances shall be installed in accordance with manufacturer's instructions.

#### 2.3 TOILET SEAT COVER DISPENSER

Surface-mounted toilet-seat cover dispenser shall be of stainless steel, all welded construction. Exposed surfaces shall have satin finish. Dispenser shall have a concealed opening in bottom for filling. Capacity shall be 250 paper toilet-seat covers.

#### 2.4 PAPER TOWEL DISPENSER AND WASTE RECEPTACLE

The combination paper towel dispenser and waste receptacle shall be surface mounted, stainless cabinet with satin finish and shall use c-fold paper sheet towels. Towel sheets shall be furnished with the dispenser. The waste receptacle cabinet shall have a 12 gallon capacity waste receptacle, having hooks and provided with a heavy vinyl liner; approximate size 17 inches wide, 29 inches high, 8 inches deep; with stainless steel skirt for surface mounting.

#### 2.5 MIRROR SHELF

The mirror shelf combination shall be surfaced mounted, polished finish stainless steel frame with mitered corners arranged to permit easy mirror

replacement; 5 inches wide, satin finish, stainless steel shelf with return edges, either integral with or securely attached to mirror frame; and mirror of 1/4 inches No. 1 quality float glass, silvered, electro-copper plated, and the back protected by shock absorbing material and heavy gauge galvanized steel plate; provided with concealed hanger and vandal-proof locking screws.

## 2.6 SOAP DISPENSER

The soap dispenser shall be for a waterless skin cleaner container and shall be made of stainless steel with satin finish. Eight 1-gallon containers of the waterless skin cleaner shall be furnished.

## 2.7 TOILET TISSUE DISPENSER

One toilet tissue dispenser, roll type, stainless steel with satin finish, shall be installed on the wall adjacent to the toilet. The toilet tissue dispenser shall be at a location convenient to the user. Four dozen toilet tissue rolls shall be furnished.

# PART 3 EXECUTION

## 3.1 GENERAL

The installation of all accessories shall be per the manufacturer's standards. Locations of washroom accessories shall be verified in the field and approved by the Contracting Officer.

## 3.2 TEMPORARY PROTECTION

Pipe, valves, and equipment openings shall be closed with caps or plugs during installation. Fixtures and equipment shall be tightly covered and protected against dirt, water, chemical or mechanical injury. At the completion of all work, the fixtures, material and equipment shall be thoroughly cleaned. Prior to and during installation, the pipe, equipment, materials and accessories shall be handled in such a manner as to prevent injury in any way to these items or materials.

-- End of Section --